



## Move 2500



### Assure terminal availability rate if power and network fail

Make NFC payment a seamless consumer experience  
Robust and functional to meet merchants' daily needs

- Processor**  
Cortex A5
- Memory**  
256 MB Flash, 128 MB RAM, 512 MB Flash, 128 MB RAM
- Display**  
2.4" backlit, QVGA (320x240 pixels)
- Operating System**  
Telium TETRA
- Audio**  
Support audio play with USB C Headphone
- Connectivity**  
WAN: 4G and/or 3G with fallback WiFi  
LAN: Dial-up Modem RJ45.  
Wired: Ethernet 10/100 base T RJ45
- Card Readers**  
ISO 1/2/3, 500K lifespan, EMV Level 1, 500K lifespan EMV Level 1 compliant
- Keys & Keypad**  
16 keys, raised marking, backlit, 4 Functional Keys without backlight
- Security**  
PCI PTS 5.x Online & off-line certified
- Battery**  
Li-ion: 2200mAh
- Environmental**  
Charging Temperature: 0°C to +40°C (32°F to 104°F)  
Operating temperature: -10°C to +40°C (14°F to 104°F)  
Storage temperature: -20°C to +55°C (-4°F to 131°F)  
Operating humidity: 85% non-condensing at +40°C (104°F).
- Other Standard Features**  
Up to 2 SAM slots, Integrated thermal printer, Terminal Size of 168x81x58 mm (6.6x3.2x2.3") 168x81x69 mm (6.6x3.2x2.7"), Terminal + Battery 320 g (11 oz), PCI PTS 5.x Online & off-line certified