



SP630 PRO



The SP630 Pro is a classic handheld POS terminal.

This latest evolution of the best-selling SP630 series provides merchants with a powerful and versatile payment acceptance solution.

- OS**
Linux
- CPU**
32-bit ARM Cortex-A7 secure processor, 1.2GHz
- Memory**
256MB RAM, 256MB FLASH 512MB RAM, 512MB FLASH
MicroSD
- Display**
2.8-inch TFT full color LCD display, resolution of 320 x 240,
Resistive touchscreen, support electronic signature
- Wireless communication**
4G/3G/2G, Bluetooth, WIFI (802.11 b/g/n)
- Magnetic card reader**
Triple track, bi-directional, conforming to ISO
7810/7811/7813
- Smart card reader**
EMV L1/L2, conforming to ISO 7816, 1.8V/3V/5V,
synchronous & asynchronous, T=0 & T=1
- Contactless card reader**
EMV Contactless L1, conforming to ISO 14443 Type A/B,
Mifare, Felica
- Scanner**
Built-in rear scanner, support 1D/2D code payment
- Printer**
High-speed thermal printer, 32lbs Paper roll diameter:
40mm Paper width: 58mm
- Audio**
Built-in buzzer, Built-in speaker, support audio prompt
- Keypad**
10 x numeric keys, 9 x function keys, 1 x power button,
backlight
- Peripheral Ports**
1 x Micro USB (OTG)
- Card Slots**
2 x SIM ,2x SAM
- Battery**
Li-ion battery, 3.6V/2500mAh/9Wh
- Power Supply**
Input: 100-240V AC, 50Hz/60Hz, 0.3A,
Output: 5.0V DC, 2.0A
- Accessories**
Flexible privacy shield, Stylus
- Dimensions**
163mm (L) x 79mm (W) x 54mm (H)
- Weight**
350g including battery
- Environment**
Operating temperature: 0°C~40°C (32°F~104 °F)
Storage temperature: -20°C~60°C (-4°F~140°F)
Relative humidity: 5%~93% (Non-condensing)
- Certifications**
PCI PTS 5.x, EMV L1/L2, EMV Contactless L1,
PayPass,payWave, American ExpressPay, Discover D-PAS,
UnionPay QuickPass, TQM, CE, RoHS