



Verifone UX300



Consider the UX300 card reader/ controller your new, most dependable employee.

This versatile, self-service solution provides secure and reliable transactions for vending machines, public transportation and other unattended, high-transaction-volume environments. Programmed to read most bank cards, chip cards and mag-stripe cards, the UX300 hybrid card reader works alone or in combination with UX Series PIN pad and NFC-reader options to add more functionality to your self-service environments.



Processor

400 MHz, ARM11 32-bit RISC processor



Display

Optional with UX 100



Physical

150mm L x 96mm W x 71mm H
(5.91 in. L x 3.78 in. W x 2.8 in. H)



Connectivity

100Mbit LAN, USB-Slave, RS232 Optional MDB, RS485, GPRS, PSTN, ISDN, 4X USB-Master, 2nd LAN



Contactless

Optional with UX 400



Security

PCI PTS 4.x approved



Memory

384MB (256MB Flash, 128MB SDRAM)



Operating System

Embedded Linux with Verifone security enhancements



Card Readers

Hybrid, triple track MSR, landed smart card, EMVCo approved



Power

12VDC power supply, optional 9VDC/42VDC, 2 power-saving modes



Mechanics (cutout)

73.2mm x 61.2mm (2.88 in. x 2.41 in.)



Environmental

-20° to 70° C (-4° to 158° F) operating temperature, -25° to 70° C (-13° to 158° F) storage temperature, 10% to 90% relative humidity, non-condensing



Other Standard Features

2 SAM slots, 3 control LEDs, buzzer, real-time clock